

Data Sheet

# VIAVI

## Network & Service Companion (NSC-100)

### Enterprise Ethernet Test

Empower techs with the simplest, most comprehensive, fastest (one-minute) service activation test and troubleshooting solution.

The NSC-100 is a test solution for Ethernet, Enterprise and Data Center Networks. It combines active Ethernet and WiFi testing capabilities enabling service activation and troubleshooting tests on all network layers.

- Simplify the Ethernet turn-up and troubleshooting process by enabling Ethernet tests on network Layers 2, 3, and 4.
- Identify and prevent customer affecting throughput issues by running active throughput tests (Speedtest, TrueSpeed RFC6349, iPerf).
- Validate business services as standalone unit, or as remote loopback device when combined with the T-BERD/MTS-5800 for Y.1564 and RFC2544 tests.
- Optimize WiFi coverage and performance; get network improvement recommendations when performance is below expectation.
- Perform 24/7 monitoring sessions for long-term, root cause failure analysis and SLA monitoring.



### Benefits

- Support of Fiber, Ethernet and WiFi in one solution
- Flexible multi-tool for enterprise and fixed-line/mobile fronthaul service installation, performance measurements and troubleshooting
- Drive compliance of both direct and contracted staff with centralized, cloud-based workflow and result management
- Remote control for leave-behind use case enables long-term testing and failure analysis
- Service activation, test and performance management (L2/L3 loopback up to 10G, TWAMP reflector)
- Centralized test system (VIAVI Fusion) leveraging NSCs as remote controlled test agents

### Features

- Ethernet test interfaces up to 10G
- Ethernet testing up to Layer 4 (TCP/UDP)
- WiFi 3x3 tests and WiFi Expert up to WiFi 6
- StrataSync and Mobile Tech app support
- Job Manager



2019 Broadband Technology Review –  
4.0 Diamond Award Winner



2022 Broadband Technology Review –  
4.0 Diamond Award Winner



2020 Lightwave Innovation Award 4.5 Winner

## Specifications

<b>GPON (Optional)</b>		
ONU/ONT Emulation	VIAVI GPON SFP	
Interface	SC/APC	
Standard	G.984.2 GPON compliant	
	G.988 OMCI compliant	
Upstream (1310 nm) Tx Signal Power Range	0.5 dBm to 5.0 dBm	
Downstream (1490 nm) Rx Signal Power Range	-28.0 dBm to -8.0 dBm	
Test Results	PON Activation State, Power Level values from the SFP, PON ID, ODN Class – according to ITU-T G.984 and G.988 standards	
<b>XGSPON (Optional)</b>		
ONU/ONT Emulation	VIAVI XGSPON SFP	
Interface	SC/APC	
Standard	G.9807.1 XGSPON compliant	
	G.988 OMCI compliant	
Upstream (1270 nm) Tx Signal Power Range	4.0 dBm to 9.0 dBm	
Downstream (1577 nm) Rx Signal Power Range	-28.0 dBm to -9.0 dBm	
Test Results	PON Activation State, Power Level values from the SFP, PON ID, ODN Class – according to ITU-T G.9807 and G.988 standards	
<b>Ethernet (Optional)</b>		
Standard	IEEE 802.3	
	10M, 100M, 1G, 2.5G, 5G, and 10G Ethernet	
Test Results	Ethernet Frames, IP Connectivity, Ping, Traceroute, Web Connectivity, Speed Test up to 2 Gbps	
TWAMP Reflector (Optional)	10M, 100M, and 1G Ethernet	
	TWAMP Light Reflector support	
Port/L2/L3 Loopback (Optional)	10M, 100M, 1G, and 10G Ethernet	
	Port Loopback and Source specific VIAVI Loopback support	
<b>WiFi (Optional)</b>		
Test Results	WiFi Expert (Passive Mode)	Up to WiFi 6 (802.11 a/b/g/n/ac/ax) <ul style="list-style-type: none"> <li>Signal strength (RSSI), Channel, Standard, Width, Channel Noise, Total Airtime, Noise Airtime, Estimated Throughput, Recommendations</li> </ul>
	OneCheck WiFi (Connected Mode)	Up to WiFi 5 3x3 (802.11 a/b/g/n/ac) <ul style="list-style-type: none"> <li>Signal strength (RSSI), Standard, Width, Max Router PHY Rate, IP/Web connectivity, Throughput Tests</li> </ul>

<b>Throughput / Performance Test (Optional)</b>	
TCP Throughput Test	VIAVI SpeedCheck Ookla Speedtest VIAVI TrueSpeed (RFC-6349) iPerf
Performance	2 Gbps for SpeedCheck, Ookla Speedtest, TrueSpeed, iPerf
Test Results	Delay, Upstream and Downstream Bit Rates
<b>User Interface</b>	
Communication Interface	Bluetooth v5.0
Smart Device Support (recommendation)	Mobile Tech app
	Android 8 or newer
	iOS 12 or newer
VIAVI Instrument Support	ONX-580, ONX-CATV
<b>General</b>	
Size	116 x 190 x 52 mm (4.6 x 7.5 x 2.0 in)
Weight	0.8 kg (1.7 lb)
Operating Temperature Range	Non-Charging: -10°C to 50°C
	Battery Charging: 0°C to 40°C
Storage Temperature Range	-20°C to 60°C
Operating Humidity Range	10% to 90% RH, non-condensing
Operating Altitude	4000 m max
DC Input Power	15V @ 3A, USB-C Power Delivery (PD)
Battery	32 W/hr Li-Ion rechargeable battery
	Field replaceable
Battery Life	1-week typical usage for installation technicians
Charge Port	USB-C
USB Host Port	USB-A (USB 3.0)

## Ordering Information

Standard Packages		
PON Package	NSC100-GPON-BASE	GPON
	NSC100-GPON-PLUS	GPON, Ethernet, SpeedCheck 1G, Speedtest 1G
	NSC100-GPON-PRO	GPON, Ethernet, WiFi, SpeedCheck 1G, Speedtest 1G
	NSC100-XGSPON-BASE	XGSPON
	NSC100-XGSPON-PLUS	XGSPON, Ethernet, SpeedCheck 1G, Speedtest 1G
	NSC100-XGSPON-PRO	XGSPON, Ethernet, WiFi, SpeedCheck 1G, Speedtest 1G
	NSC100-GPON-XGSPON-BASE	GPON, XGSPON
	NSC100-GPON-XGSPON-PLUS	GPON, XGSPON, Ethernet, SpeedCheck 1G, Speedtest 1G
	NSC100-GPON-XGSPON-PRO	GPON, XGSPON, Ethernet, WiFi, SpeedCheck 1G, Speedtest 1G
Home Package	NSC100-HOME-PLUS	Ethernet, SpeedCheck 1G, Speedtest 1G
	NSC100-HOME-PRO	Ethernet, WiFi, SpeedCheck 1G, Speedtest 1G
Enterprise	NSC100-ENTERPRISE-PLUS	Ethernet, TrueSpeed 1G
	NSC100-ENTERPRISE-PRO	Ethernet, WiFi, TrueSpeed 1G
Loopback	NSC100-LOOPBACK-BASE	Ethernet Loopback 1G
	NSC100-LOOPBACK-PLUS	Ethernet Loopback 10G
Platinum	NSC100-PLATINUM-1G	GPON, Ethernet, WiFi, SpeedCheck 1G, Speedtest 1G, TrueSpeed 1G, Loopback 1G, TWAMP
	NSC100-PLATINUM-10G	GPON, Ethernet, WiFi, SpeedCheck 2G, Speedtest 2G, TrueSpeed 2G, Loopback 10G, TWAMP
Options		
Test Applications	NSC-OC-GPON	NSC OneCheck GPON
	NSC-OC-XGSPON	NSC OneCheck XGSPON
	NSC-OC-ETHERNET	NSC OneCheck Ethernet
	NSC-OC-WIFI	NSC OneCheck WiFi
	NSC-WIFI-EXPERT	NSC WiFi Expert
Speed Tests	NSC-SPEEDCHECK-1G	NSC SpeedCheck over 1GE port up to 1Gbps
	NSC-SPEEDCHECK-2G	NSC SpeedCheck over 2.5/5/10GE port up to 2Gbps
	NSC-SPEEDTEST-1G	NSC Ookla Speedtest over 1GE port up to 1Gbps
	NSC-SPEEDTEST-2G	NSC Ookla Speedtest over 1+1/2.5/5/10GE ports up to 2Gbps
	NSC-TRUESPEED-1G	NSC TrueSpeed (RFC-6349) over 1GE port up to 1Gbps
	NSC-TRUESPEED-2G	NSC TrueSpeed (RFC-6349) over 2.5/5/10GE port up to 2Gbps
	NSC-IPERF-1G	NSC iPerf Test over 1GE port up to 1Gbps
	NSC-IPERF-2G	NSC iPerf Test over 2.5/5/10GE port up to 2Gbps
Enterprise	NSC-LOOPBACK-1G	NSC L2/L3 1G Loopback
	NSC-LOOPBACK-10G	NSC L2/L3 10G Loopback
	NSC-FUSION-CLIENT	NSC Fusion Client
	NSC-TWAMP-REFLECTOR	NSC TWAMP Reflector
	NSC-OPTICAL-ETHERNET	NSC Optical Ethernet

## Ordering Information continued

Options continued		
SFP	NSC-SFP-ELEC-1G	NSC 1G Electrical Ethernet SFP
	NSC-SFP-ELEC-AUTO-10G	NSC 2.5G, 5G and 10G Autoneg Electrical Ethernet SFP+
	NSC-SFP-ELEC-1-2.5-5-10G	NSC 1G, 2.5G, 5G and 10G Electrical Ethernet SFP+
	NSC-SFP-850-1G-10G	NSC 1G and 10G Optical Ethernet SFP+ 850 nm SR
	NSC-SFP-1310-1G-10G	NSC 1G and 10G Optical Ethernet SFP+ 1310 nm LR
	NSC-SFP-1550-1G-10G	NSC 1G and 10G Optical Ethernet SFP+ 1550 nm ER
	NSC-SFP-GPON	NSC GPON SFP
	NSC-SFP-XGSPON	NSC XGSPON SFP+
Optional Accessory		
	NSC-CAR-CHARGER	NSC Car Charger with Cable
Replacement Parts		
	NSC-BATTERY	NSC Battery
	NSC-CHARGER	NSC Charger with Cable
	NSC-STRAP	NSC Hand Strap
	NSC-CASE	NSC Carrying Case
	NSC-ETHERNET-ADAPTER	Ethernet Cat6a M-Adapter Cable
	NSC-ETHERNET-CABLE	Ethernet Cat6a M-M Patch Cable



Contact Us **+1 844 GO VIAVI**  
(+1 844 468 4284)

To reach the VIAVI office nearest you,  
visit [viasolutions.com/contact](https://viasolutions.com/contact)

© 2023 VIAVI Solutions Inc.  
Product specifications and descriptions in this document are subject to change without notice.  
Patented as described at  
[viasolutions.com/patents](https://viasolutions.com/patents)  
nsc100-ethernet-ds-xpf-nse-ae  
30190934 908 0223