

CX200 SiteXpert

Functional Specifications

General Specifications

Dimensions	11.2 in. (284.3 mm) x 6.8in. (173.5 mm) x 4.2 in. (106.8 mm)
Weight	8.6 lbs
Display	8 in. (203.2 mm)
Environmental	
Operating Temperature	0 to 50°C
Non-Operating	-40 to 71°C (battery removed)
Relative Humidity	95% non-condensing
Altitude	4600 m
Vibration	MIL-PRF-28800F Class 3
Shock Functional	MIL-PRF-28800F Class 3
Bench Handling	MIL-PRF-28800F Class 3
Transit Drop	MIL-PRF-28800F Class 3
Warm-up Time	30 min
Battery	
Type	14.4 V, 6.8 Ah (Lithium Ion)
Operating Temperature	-20°C to 60°C battery temperature
Charging Temperature	0°C to 45°C battery temperature
Storage Temperature	-20°C to 60°C
Weight	1 lbs.
Runtime	3 Hours
Compliance	
EMC	IEC/EN 61326-1:2006, CISPR11:2009 +A1:2010
Safety	EN 61010-1, 3rd Edition



General Specifications continued

Timebase	
Temperature Stability	0.05 ppm (0 - 50°C)
Aging	0.5 ppm/year
Ports	
<i>RF Output</i>	
Type	N-Type
Impedance	50 Ω
Reverse Power Input	35 dBm max frequency ≥1 MHz
VSWR	≤1.6:1 typical for frequency >1 MHz
<i>RF Input</i>	
Type	N-Type
Impedance	50 Ω
Power Input, Damage Level	27 dBm max min gain and frequency ≤1 MHz
	21 dBm max other gains and frequency ≥1MHz
Power Input, Nominal Power	10 dBm max nominal power
	±50 Vdc max
VSWR	≤1.7:1 typical for frequency 1 MHz to 3 GHz
<i>Duplex</i>	
Type	N-Type
Impedance	50 Ω
Power Input	47 dBm max (50 W continuous, temperature ≤35°C ambient)
	51 dBm max (125 W, 30 seconds on, 90 seconds off)
VSWR	≤1.2:1
<i>Audio In 1</i>	
Type	BNC
Selectable Impedance	300 Ω, 600 Ω, 100 k Ω single ended, ±1 % shunted by ≤ 300 pF
	200 k Ω differential, ±8 %
Max Input Voltage	200 V
Max Input Power	1.5 W
<i>Audio In 2</i>	
Type	BNC
Max Input Voltage	7 Vrms
Max Input Power	1.5 W

General Specifications continued

Audio AF Out

Type	BNC
Impedance	$\leq 4 \Omega$
Max Output Current	100 mA typical

Mic/Accessory Connector

Connector	8 pin, standard Din (SDF-80J)
Voltage Source	8 V @ 150 mA or Battery Voltage 11 V to 28 V @ 2.0 A
PTT Output	Open Collector, +10 V max, 20 mA sink
PTT Input	5.0 V pullup, 5 mA

RF Generator

Frequency

Range	1 MHz to 3 GHz
Resolution	0.1 Hz
Accuracy	Same as timebase

Amplitude

RF Out	
Range	0 to -65 dBm
Accuracy	1.5 dB
Duplex	
Range	-50 to -135 dBm
Accuracy	1.5 dB
Resolution	0.1 dB

Spectral Purity

Harmonics	≤ -40 dBc, (-50 dBc Typical)
Non-harmonics	≤ -40 dBc, (-50 dBc typical)
Phase Noise	-95 dBc/Hz at 10 kHz
Residual FM	<15 Hz RMS in 300 Hz to 3 kHz BW, <6 Hz RMS, Typical <800 MHz
Residual AM	<0.5% RMS in 300 Hz to 3 kHz BW

Analog Modulation

Sources

Number	2
Type	Internal
Mode	Analog (AM, FM)
Rate	0 Hz to 20 kHz
Distortion THD	3% (1000 Hz rate, >2 kHz Deviation, 300 Hz - 3 kHz BP filter)

General Specifications continued

AM Modulation

Range	0 to 100%
Resolution	0.1%
Accuracy	10% setting (150 Hz to 5 kHz rate, 10% to 90% modulation)
Flatness	±0.5 dB from 20 Hz to 10 kHz

FM Modulation

Range	0 to 100 kHz
Resolution	1 Hz
Accuracy	≤±2.5% of settings
Flatness	±0.5 dB from 20 Hz to 10 kHz

Digital Modulation

Mode	P25
------	-----

RF Power Meter

Frequency

Range	1 MHz to 3 GHz
Bandwidth	5 kHz, 6.25 kHz, 8.33 kHz, 10 kHz, 12.5 kHz, 25 kHz, 30 kHz, 100 kHz, and 300 kHz

Amplitude

RF Input Port	10 dBm to -108 dBm
Duplex Port	45 dBm to -67 dBm Note: Minimum calculated for 5 kHz BW, 16 dB SNR for 0.1 dB noise contribution

Accuracy After Normalizing at the Measurement Frequency

Duplex Port	±0.4 dB (frequency ≤1 GHz and ≥1 MHz), ±0.6 dB (elsewhere)
RF Input Port	±0.6 dB (frequency ≤1 GHz and ≥1 MHz), ±0.9 dB (elsewhere)

RF Frequency Meter

Frequency

Range	1 MHz to 3 GHz
Resolution	1 Hz
Frequency Find	≤2 seconds
Accuracy	Same as timebase

RF Analyzer (Channel Analyzer)

Frequency

Range	1 MHz to 3 GHz
Resolution	0.1 Hz
Accuracy	Same as timebase

General Specifications continued

Spurious	
Input Related	≤ -65 dBc typical
Non-Input Related	≤ -95 dBm typical
Analysis	
RBW	1 Hz to 50 kHz in 1,2,5 sequence
Amplitude	
Range	RF Input port: +10dBm max, minimum limited by DANL Duplex port: +45dBm max, minimum limited by DANL
Displayed Average Noise Level in 1 Hz RBW	
RF Input Port	< -162 dBm/Hz at max gain
Duplex Port	< -120 dBm/Hz at max gain
RF Analyzer (Modulation Analyzer)	
General Analysis Specification	
Analysis Bandwidth	8 MHz, 100 MHz wideband option
Demodulation Bandwidth	5 kHz, 6.25 kHz, 8.33 kHz, 10 kHz, 12.5 kHz, 25 kHz, 30 kHz, 100 kHz, and 300 kHz
Post-Demodulation Low-pass Filters	300 Hz, 3 kHz, 3.4 kHz, 5 kHz, 15 kHz, and 20 kHz
Post-Demodulation High-pass Filters	20 Hz, 50 Hz, 300 Hz
Post-Demodulation Band-pass Filters	CCITT, A-weighted, C-weighted, C-message
Post-Demodulation Deemphasis Filters	75 μ s, 750 μ s
Amplitude	
RF Input Port	+20 dBm (+13 dBm ≤ 1 MHz) to -80 dBm (with preamp enabled)
Duplex Port	+51 dBm to -20 dBm
FM Demodulation	
Detectors	RMS, $\sqrt{2}$.RMS, +Pk, -Pk, \pm Pk/2
Deviation	0 Hz to 75 kHz (peak)
Rate	10 Hz to 20 kHz
Resolution	0.1 Hz
Accuracy	± 1 % for deviation ≥ 1.5 kHz and ≤ 3 kHz at 1 kHz rate ± 2 % otherwise
Distortion	± 0.5 % for rate ≤ 3 kHz ± 1.0 % otherwise
Residual	≤ 3 Hz for post-detection BW 300 Hz to 3 kHz and RF frequency ≤ 1 GHz

General Specifications continued

AM Demodulation

Detectors	RMS, $\sqrt{2}$.RMS, +Pk, -Pk, $\pm Pk/2$
Depth	0% to 100%
Rate	10 Hz to 20 kHz
Resolution	0.1%
Accuracy	$\pm 1\%$ for depth $\geq 30\%$ and $\leq 90\%$ at 1 kHz rate $\pm 2\%$ otherwise
Distortion	$\pm 0.5\%$ for rate ≤ 3 kHz $\pm 1.0\%$ otherwise
Residual	$\leq 0.1\%$ for post-detection BW 300 Hz to 3 kHz and RF frequency ≤ 1 GHz

SSB Demodulation

Mode	LSB, USB
Power	RMS, $\sqrt{2}$.RMS, Pk
Rate	10 Hz to 20 kHz
Resolution	0.1 Hz

Digital Demodulation

Mode	P25
------	-----

P25 Measurements

Modulation Fidelity	$\leq 5\%$ of reading (2.5 to 12 %)
Symbol Deviation	$\pm 1\%$
Frequency Error	Timebase ± 0.5 Hz
Symbol Rate Error	Timebase ± 0.1 ppm

Spectrum Analyzer

Frequency

Range	1 MHz to 3 GHz
Resolution	1 Hz
Frequency Span	0 Hz (zero span) to 3 GHz (full span)
Accuracy	Same as timebase

Spectral Purity

Phase Noise	-95 dBc/Hz at 10 kHz
Spurious	
Input Related	≤ -65 dBc typical
Non-Input Related	≤ -95 dBm typical

General Specifications continued

Analysis	
RBW	25 Hz to 6 MHz
RBW Mode	Auto (ratio of span), Manual
Trace Detectors	Normal, +Pk, -Pk, Sample, Average (RMS)
Sweep Time	0.4 ms to 1000 s
Sweep Time Mode	Auto, Manual
VBW	5 Hz to 6 MHz
VBW Mode	Auto, Manual
Trace Point Range	101 to 8192
Trigger	
Sources	Free run, External, Video
Delay	1 μ s to 500 ms
	-150 ms to 500 ms (zerospan)
Resolution	1 μ s
Displayed Average Noise Level in 1 Hz RBW	
RF Input Port	<-162 dBm/Hz at max gain
Duplex Port	<-120 dBm/Hz at max gain
Third-Order Intercept	
RF Input Port	IIP3 > 37 dBm
Duplex Port	IIP3 > 37 dBm
	2 CW tones 4 dBm, 10 kHz apart
Tracking Generator	
Output Ports	RF Output Port, RF Duplex Port
Level	
Range	Same as RF Generator
Accuracy	Same as RF Generator
AF Function Generator	
Frequency Specifications	
Range	20 Hz to 20 kHz (± 0.2 dB)
	DC to 100 kHz (± 0.5 dB)
Resolution	0.1 Hz
Accuracy	Same as timebase

General Specifications continued

<i>Amplitude Specifications</i>	
Range	0 to ±8 Vpk into 600 Ω
	0 to ±4 Vpk into 50 Ω
DC Accuracy	±2 %
AC Accuracy	±2 % (level ≥200 mV and frequency from 20 Hz to 20 kHz)
	±5 % (level ≥2 mV and frequency from 20 Hz to 100 kHz)
Residual THD+Noise	≤75 dB for frequency 1 kHz and level 1 Vrms
AF Composite Signals	Sine, Square, DTMF, DCS, Two-Tone, Tone Remote, Tone Sequential,

AF Analyzer

<i>Channels</i>	
Number	2 single ended or 1 double ended combining Audio 1 and Audio 2
	Microphone input is routed through Audio 2

<i>Frequency Specifications</i>	
Range	20 Hz to 20 kHz (±0.2 dB)
	DC to 100 kHz (±0.5 dB)

<i>Amplitude Specifications</i>	
Range	20 mV to 30 Vrms, auto-ranging
DC Accuracy	±2% of reading
AC Accuracy	±2% of reading (level ≥200 mV and freq from 20 Hz to 20 kHz)
	±5% of reading (level ≥20 mV and freq from 20 Hz to 100 kHz)
	±10% of reading for Mic input (freq from 100 Hz to 15 kHz)
Residual THD+Noise	≤75 dB for frequency (20 Hz to 20 kHz single-ended 1 Vrms)
CMRR	≥60 dB typical for differential input
AF Composite Signals	Sine, Square, DTMF, DCS, Two-Tone, Tone Remote, Tone Sequential

Audio and Demodulation Meters

<i>Distortion Meter</i>	
Frequency Range	50 Hz to 10 kHz
Level Range	50 mVrms to 30 Vrms
Measurement Range	0 to 100%
Resolution	0.1%
Accuracy	≤3% of reading + 0.1% distortion for 1% to 20%

General Specifications continued

SINAD meter

Frequency Range	50 Hz to 10 kHz
Level Range	50 mVrms to 30 Vrms
Measurement Range	0 to 60 dB
Resolution	0.1 dB
Accuracy	≤1 dB @ 12 dB SINAD

Frequency Counter

Frequency Range	300 Hz to 20 kHz
Resolution	0.1 Hz
Accuracy	Timebase ±1 Hz
Tone Analyzer Modes	DTMF, DCS, Two-Tone, Tone Sequential, Tone Remote

Audio FFT Analyzer

Frequency Range	DC to 100 kHz
Level Range	50 mVrms to 30 Vrms
Resolution	0.1 Hz
Accuracy	Timebase ±1 Hz
Level Accuracy	Same as Audio Frequency Analyzer
Filters	Same as Audio Frequency Analyzer and Modulation Analyzer

Vector Network Analyzer

Frequency

Range	1 MHz to 3 GHz
Resolution	0.1 Hz
Accuracy	Same as timebase

Test Port Power

Dynamic Range	90 dB
---------------	-------

Measurements

Parameters	S ₁₁
Graph Type	Log Magnitude (dB), SWR (Linear)
Domains	Frequency, Distance
Calibration Type	Full S ₁₁
Calibration Method	Short-Open-Load
Corrected Accuracy	Source Match > 30 dB Reflection Tracking ±0.5 dB

General Specifications continued

<i>Distance Domain</i>	
Maximum Distance	100 m (327.75 ft) or 40 dB Return Loss, whichever comes first for a 3 GHz span
Measurement Display	Return Loss, VSWR
Measurement Format	dB, VSWR



viavisolutions.com

Contact Us: +1 800 835 2352

avcomm.sales@viavisolutions.com

© 2025 VIAVI Solutions Inc.

Product specifications and descriptions in this document are subject to change without notice.
Patented as described at viavisolutions.com/patents

cx200-ds-avi-nse-ae
30194346 900 0325